
PRODUCT INFORMATION



A Product of Valvoline Cummins Ltd.

Valvoline XLD Plus 10W

PRODUCT DESCRIPTION

Valvoline XLD Plus 10W is blended from high refined base stocks incorporating carefully selected detergent, dispersant and anti-oxidant additives to give the desired performance.

APPLICATION

Valvoline XLD Plus 10W is recommended for use in naturally aspirated and turbo-charged heavy duty diesel engines of heavy vehicles, earthmoving equipments operating under low ambient temperatures. The product is also recommended as hydraulic fluid type C2 specification of Detroit Diesel, Allison Division of General Motors, Komatsu and Caterpillar transmission systems

PERFORMANCE STANDARDS

BIS	13656 : 1993, E-DL2
US Military	MIL-L-45199B
Caterpillar	Series III
General Motors	
Allison Division,	C2 Type Fluids

TYPICAL CHARACTERISTICS

Kinematic Viscosity @ 40°C, cSt	35
Kinematic Viscosity @ 100°C, cSt	5.95
Viscosity Index	114
Flash Point, COC, °C	230
Pour Point, °C	-27
TBN, mg KOH/g	7.2

Available Packs: 20, 210 Ltrs.

1/2004



Valvoline Cummins Ltd.
A Joint Venture Company of
Valvoline International Inc., USA
& Cummins Diesel Sales and Service (India) Ltd.
52, Okhla Industrial Estate, Phase III, New Delhi – 110 020
Phone: (011) 51613444 – 48, Fax: (011) 51613453
Visit us at: www.valvolinecummins.com

